

Output Ratings		
Generating Set Model	P27P1	P30E1
380 – 415V, 50 Hz	27.0 kVA 21.6 kW	30.0 kVA 24.0 kW
480V, 60 Hz	30.0 kVA 24.0 kW	34.0 kVA 27.2 kW

Ratings at 0.8 pf

Ratings Definitions

Prime Power – Model P27P1

These ratings are applicable for supplying continuous electrical power (at variable load) in lieu of commercially purchased power. This model can supply 10% overload power for 1 hour in 12 hours.

Standby Power – Model P30E1

These ratings are applicable for supplying continuous electrical power (at variable load) in the event of a utility power failure. No overload is permitted on these ratings. The alternator model is peak continuous rated (as defined in ISO 8528-3).

Technical Data		
Engine Model:	Perkins 1103A-33G	
Alternator Model:	LL1014Q	
Number of Cylinders:	3 in line	
Displacement: Litres (cu.in)	3.3 (201.4)	
Bore/Stroke: mm (in)	105.0 (4.1) / 127.0 (5.0)	
Compression ratio:	19.25:1	
Induction:	Naturally Aspirated	
Frequency:	50 Hz	60 Hz
Engine Speed:	1500 RPM	1800 RPM
Gross Engine Power: kW (hp)	31.0 (42.0)	36.5 (49.0)
BMEP: kPA (psi)	752.0 (109.0)	738.0 (107.0)
Piston Speed: m/sec (ft/sec)	6.4 (20.8)	7.6 (25.0)
Fuel Tank Capacity: Litres (US Gal)	144 (38.0)	144 (38.0)
Fuel Consump, P27P1: 1/hr (USg/hr)	6.3 (1.7)	7.3 (1.9)
Fuel Consump, P30E1: 1/hr (USg/hr)	7.0 (1.8)	8.2 (2.2)
Heat Rejected to Exhaust System: kW (Btu/min)	21.9 (1245)	29.9 (1700)
Heat Rejected to Water & Lube Oil: kW (Btu/min)	13.5 (768)	19.4 (1103)
Heat Radiated to Room: kW (Btu/min)	8.4 (478)	8.8 (500)
Exhaust Gas Temperature: °C (°F)	TBA	TBA
Radiator Cooling Air Flow: m³/min (cfm)	69.6 (2458)	90.6 (3200)
Combustion Air Flow: m³/min (cfm)	2.5 (88)	2.9 (102)
Exhaust Gas Flow: m³/min (cfm)	TBA	TBA

Note: Standard reference conditions 27°C (80°F) Air Inlet Temp, 152.4m (500ft) A.S.L. 60% relative humidity. All engine performance data based on the above mentioned maximum continuous ratings. Fuel consumption data at full load with diesel fuel with specific gravity of 0.85 and conforming to BS2869: 1998, Class A2.

Dimensions and Weights				
Length: mm (in)	Width: mm (in)	Height: mm (in)	Dry: kg (lb)	Wet: kg (lb)
1770 (69.7)	714 (28.1)	1368 (53.9)	785 (1731)	800 (1764)
Dry = With Lube Oil		Wet = With Lube Oil and Coolant		

Generating set pictured may include optional accessories



P27P1 – P30E1



FG Wilson (Engineering) Ltd
 Old Glenarm Road, Larne, County Antrim BT40 1EJ
 Northern Ireland, United Kingdom
 Tel: +44 (0) 28 2826 1000 Fax: +44 (0) 28 2826 1111
www.FGWilson.com

